



Premium Roofing Building Materials - Technology Data Sheet

Exposure Guidelines: Fontana uses 2 weathering tests to arrive at the recommended maximum exposure times.

Fontana's Vulca Seal products are not designed to be left permanently exposed to weather/elements. Membranes should be covered with the final product as soon as possible to prevent the initial stages of degradation.

Recommended Maximum Monthly Exposure	
15# ASTM	1
2 Ply 15# ASTM	2
30# ASTM	3
2 Ply 30# ASTM	6
40# Organic Base	6
G40 Modified Fiberglass	5
Acrlay	5

Underlayment	Length	Width	SQ	Rolls Per Pallet	Pallet Per Truck	Specification	Certification
Vulca Seal ASTM 15#	144'	36"	4	30	30	ASTM D226 TYPE I ASTM D4869 TYPE I	UL ER 18554-01 UL TYPE 15
Vulca Seal ASTM 15# Perforated	144'	36"	4	30	30	ASTM D226 TYPE I ASTM D4869 TYPE I	UL ER 18554-01 UL TYPE 15
Vulca Seal ASTM 30#	72'	36"	2	25	34	ASTM D226 TYPE II ASTM D4869 TYPE IV	UL ER 18554-01 UL TYPE 30
Vulca Seal ASTM 30#, 18" Shake Felt	120'	18"	1	32	28	ASTM D226 TYPE II ASTM D4869 TYPE IV	UL ER 18554-01 UL TYPE 30
Vulca Seal ASTM 30#, 22" Shake Felt	120'	22"	1	32	26	ASTM D226 TYPE II ASTM D4869 TYPE IV	UL ER 18554-01 UL TYPE 30
Vulca Seal Organic 40#	72'	36"	2	27	21	ASTM D2626	UL ER 18554-01 UL BASE SHEET
Vulca Seal G40 Fiberglass	66'	39.37"	2	36	16	ASTM D6757 ASTM D4601 TYPE II	UL GLASS BASE
Fontana 15# 4SQ	144'	36"	4	36	32	ASTM D4869 TYPE I	N/A
Fontana 15# 3SQ	108'	36"	3	42	34	ASTM D4869 TYPE II	N/A
Fontana 30#	72'	36"	2	36	36	ASTM D4869 TYPE III	N/A
Vulca Seal Acrlay Partially Adhered	70.5'	39.37"	2	30	19	ASTM 6757 ASTM 4601 TYPE II	UL GLASS BASE

* Truck load qty's may vary

*** Exposure tests are NOT conducted past 6 month***

Delivering Quality Materials for Generations!

Fontana Paper Mills, Inc.
13733 Valley Blvd
Fontana, CA 92335
(909) 823-4100

WWW.FONTANAROOF.COM

2020 EDITION